

MSDS MPT Diesel Fuel System Conditioner

1. Product Identification

MPT Industries
6-B Hamilton Business Park
85 Franklin Road
Dover NJ 07801
Phone: 973-989-9220
www.mptindustries.com

Synonyms: Diesel Fuel Conditioner/Additive

Molecular Weight: Not applicable to mixtures.

Chemical Formula: Mixture

Part # : MPT31, MPT32, MPT119

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent
Trade Secret Additives	(non-hazardous)	15-25%
EthylHexyl Nitrate	27247-96-7	15-25%
EthylHexanol	104-76-7	5-15%
Petroleum Naptha	64742-47-8	35-45%

3. Hazards Identification

Emergency Overview

DANGER! HARMFUL OR FATAL IF SWALLOWED. AFFECTS CENTRAL NERVOUS SYSTEM. MAY AFFECT KIDNEYS. FLAMMABLE LIQUID AND VAPOR. HARMFUL IF INHALED. CAUSES IRRITATION TO SKIN, EYES, AND RESPIRATORY TRACT.

Health Rating: 2 - Moderate

Flammability Rating: 2 - Moderate

Reactivity Rating: 0 - None

Contact Rating: 1 - Slight

Lab Protective Equip: GOGGLES; LAB COAT; VENT HOOD; PROPER GLOVES; CLASS B EXTINGUISHER.

Potential Health Effects

Inhalation:

Effects are typically those of most hydrocarbons, dizziness, and euphoria leading to unconsciousness in severe cases. Vapors also irritate the respiratory tract. Symptoms may include coughing, difficult breathing, and chest pain. A central nervous system depressant.

Ingestion:

Fatal dose for humans estimated at 3-4 oz, but ingestion of much smaller amounts may cause lung edema and possible death because of aspiration into lungs.

Skin Contact:

The defatting action of this solvent may lead to soreness, inflammation and, possibly, dermatitis.

Eye Contact:

Vapors may be irritating at concentrations of 450 ppm and above (15 minutes exposure) and contact with the liquid solvent can be painful and possibly damaging to eye tissues.

Chronic Exposure:

Chronic exposure may lead to central nervous system complications, blood changes (aplastic anemia, a rare occurrence that is potentially fatal), and dermatitis. Animal studies have indicated the potential for liver and kidney damage.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or eye problems or impaired kidney function may be more susceptible to the effects of the substance.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion:

Aspiration hazard. If swallowed, vomiting may occur spontaneously, but DO NOT INDUCE. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Never give anything by mouth to an unconscious person.

Call a physician immediately.

Skin Contact:

Immediately flush skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Flash point: 188 F

Upper Flammable Limit: Not determined

Lower Flammable Limit: Not determined

Autoignition Point: Not determined

Water Solubility: Not soluble

Explosion Data: Does not have explosive properties

Volatile Organic Compound: Not determined

Fire Extinguishing Media:

Dry chemical, foam, or carbon dioxide. Direct stream of water can scatter and spread flames.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full-face piece operated in the pressure demand or other positive pressure mode. Water spray may be used to keep fire-exposed containers cool.

6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e.g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

7. Handling and Storage

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Do not attempt to clean empty containers since residue is difficult to remove. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, sparks, flame, static electricity, or other sources of ignition: they may explode and cause injury or death.

8. Exposure Controls/Personal Protection

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details. Use explosion-proof equipment.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a half-face organic vapor respirator may be worn for up to ten times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece organic vapor respirator may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Rubber or neoprene gloves and additional protection including impervious boots, apron, or coveralls, as needed in areas of unusual exposure.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eyewash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Brown liquid.

Odor:

Kerosene-like.

Solubility:

Insoluble in water.

Density:

0.91

pH:

No information found.

Melting Point:

No information found.

Vapor Density:

No information found.

Vapor Pressure

No information found..

Evaporation Rate:

No information found.

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Carbon dioxide, carbon monoxide, hydrogen, nitrogen, propylamine, and aliphatic alcohols may be released.

Incompatibilities:

Strong acids, strong oxidizers.

Conditions to Avoid:

Not determined.

MSDS MPT Diesel Fuel System Conditioner

11. Toxicological Information

-----\Cancer Lists\-----			
	---NTP Carcinogen---		
Ingredient	Known	Anticipated	IARC Category
-----	-----	-----	-----
EthylHexanol			

12. Ecological Information

Environmental Fate:

No information found.

Environmental Toxicity:

No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state, and local requirements.

14. Transport Information

DOT Proper Shipping Name: Not applicable

DOT Hazardous Class: Not applicable

IMO Class: Not applicable

EPA Hazardous Substances: Not known to contain greater than 1% of any SARA Extremely Hazardous Substances

California Proposition 65: May contain detectable amounts of a Ethylene Oxide and Naphthalene which are known to cause cancer in the state of CA.

15. Regulatory Information

U.S. TSCA Inventory: All components are included on the U.S. TSCA inventory or are exempt.

16. Other Information

NFPA Ratings: Health: 2 Flammability: 2 Reactivity: 0

Label Hazard Warning:

DANGER! HARMFUL OR FATAL IF SWALLOWED. AFFECTS CENTRAL NERVOUS SYSTEM. MAY AFFECT KIDNEYS. FLAMMABLE LIQUID AND VAPOR. HARMFUL IF INHALED. CAUSES IRRITATION TO SKIN, EYES, AND RESPIRATORY TRACT.

Label Precautions:

Keep away from heat, sparks, and flame.

Avoid breathing vapor.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.
Avoid contact with eyes, skin, and clothing.

Label First Aid:

Aspiration hazard. If swallowed, vomiting may occur spontaneously, but DO NOT INDUCE. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Never give anything by mouth to an unconscious person. Call a physician immediately. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention.

Product Use:

Diesel Fuel System Additive

Disclaimer:

MPT Industries provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.